

METHES

energies

B-100 BIODIESEL

TRANSPORT INFORMATION

UN HAZARD CLASS: N/A

NMFC (National Motor Freight Classification):

PROPER SHIPPING NAME: Fatty acid ester

IDENTIFICATION NUMBER: 144920

SHIPPING CLASSIFICATION: 65

CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Methes Energies Canada Inc.

5-4170 Sladeview Crescent

Mississauga, Ontario, L5L 0A1

Tel: 905.828.2700

Effective Date: 01/Jan/2006

General Product Name: Biodiesel

Synonyms: Methyl Soyate, Rapeseed Methyl Ester (RME),
Methyl Tallowate

Product Description: Methyl esters from lipid sources

CAS Number: Methyl Soyate: 67784-80-9;

RME: 73891-99-3; Methyl Tallowate: 61788-71-2

FIRST AID MEASURES

EYES:

Irrigate eyes with a heavy stream of water for at least 15-20 minutes.

SKIN:

Wash exposed areas of the body with soap and water.

INHALATION:

Remove from area of exposure, seek medical attention if symptoms persist.

INGESTION:

Give one or two glasses of water to drink. If gastro-intestinal symptoms develop, consult medical personnel. (Never give anything by mouth to an unconscious person.)

FIRE FIGHTING MEASURES

Flash Point (Method Used): 130.0_C min (ASTM 93)

Flammability: None known

EXTINGUISHING MEDIA:

Dry chemical, foam, halon, CO₂, water spray (fog). Water stream may splash the burning liquid and spread fire.

SPECIAL FIRE FIGHTING PROCEDURES:

Use water spray to cool drums exposed to fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Oil soaked rags can cause spontaneous combustion if not handled properly. Before disposal, wash rags with soap and water and dry well ventilated area. Firefighters should use self-contained breathing apparatus to avoid exposure to smoke and vapor.

HANDLING AND STORAGE

Store in closed containers between 50°F and 120°F.

Keep away from oxidizing agents, excessive heat, and ignition sources.

Store and use in well ventilated areas.

Do not store or use near heat, spark, or flame, store out of sun.

Do not puncture, drag, or slide this container.

Drum is not a pressure vessel; never use pressure to empty.

EXPOSURE CONTROL/PERSONAL PROTECTION

RESPIRATORY PROTECTION:

If vapors or mists are generated, wear a NIOSH approved organic vapor/mist respirator.

PROTECTIVE CLOTHING:

Safety glasses, goggles or face shield recommended to protect eyes from mists or splashing. PVC coated gloves recommended to prevent skin contact.

OTHER PROTECTIVE MEASURES:

Employees must practice good personal hygiene, washing exposed areas skin several times daily and laundering contaminated clothing before re-use.

PHYSICAL AND CHEMICAL PROPERTIES

Boiling point, 760 mm HG: >200_C

Specific Gravity (H₂O=1): 0.88

Vapor Pressure, mm HG: <2

Vapor Density, Air=1: >1

Volatiles, % by Volume: <2

Solubility in H₂O, % by Volume: insoluble

Evaporation Rate, Butyl Acetate=1: <1

Appearance and Odor: pale yellow liquid, mild odor

STABILITY AND REACTIVITY

GENERAL:

This product is stable and hazardous polymerization will not occur.

INCOMPATIBLE MATERIALS AND CONDITIONS TO AVOID:

Strong oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS:

Combustion produces carbon monoxide carbon dioxide along with thick smoke.

DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:

Waste may be disposed of by a licensed waste disposal company.

Contaminated absorbent material may be disposed of in an approved landfill. Follow local, province, and federal disposal regulations.

ACCIDENTAL RELEASE MEASURES SPILL CLEAN-UP PROCEDURES

Remove sources of ignition, contain spill to smallest area possible.

Stop leak if possible. Pick up small spills with adsorbent materials such as paper towels. "Oil Dry", sand or dirt. Recover large spills for salvage or disposal. Wash hard surfaces with safety solvent or detergent to remove remaining oil film. Greasy nature will result in a slippery surface.

COMPOSITION/INFORMATION ON INGREDIENTS

This product contains no hazardous materials.

OTHER INFORMATION:

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. Such information is to the best of the company's knowledge and believed accurate and reliable as of the date indicated. However, no representation, warranty or guarantee of any kind, express or implied, is made as to its accuracy, reliability or completeness and we assume no responsibility for any loss, damage or expense, direct or consequential, arising out of use. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use.

REGULATORY INFORMATION:

OSHA STATUS:

This product is not hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29 CFR 1910.1200. However, thermal processing and decomposition fumes of this product may be hazardous as noted in Sections 2 and 3.

TSCA STATUS:

This product is listed on TSCA. CERCLA (Comprehensive Response Compensation and Liability Act):

NOT reportable.

SARA TITLE III (Superfund Amendments and Reauthorization Act):
Section 312 Extremely Hazardous Substances:

None

Section 311.312 Hazard Categories:

Non-hazardous under Section 311/312

Section 313 Toxic Chemicals:

None

RCRA STATUS:

If discarded in its purchased form, this product would not be a hazardous waste either by listing or by characteristic. However, under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as hazardous waste, (40 CFR 261.20-24)

HAZARDS IDENTIFICATION

Potential Health Effects:

INHALATION:

Negligible unless heated to produce vapors. Vapors or finely misted materials may irritate the mucous membranes and cause irritation, dizziness, and nausea. Remove to fresh air.

EYE CONTACT:

May cause irritation. Irrigate eye with water for at least 15-20 minutes. Seek medical attention if symptoms persist.

SKIN CONTACT:

Prolonged or repeated contact is not likely to cause significant skin irritation. Material is sometimes encountered at elevated temperatures. Thermal burns are possible.

INGESTION:

No hazards anticipated from ingestion incidental to industrial exposure.

Corporate Head Office

5-4170 Sladeview Crescent

Mississauga, Ontario, L5L 0A1

Tel: 905.828.2700